

United States Patent and Trademark Office



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/828,438	04/21/2004	Hayato Nakanishi	119128	7096
25944 7590 06/22/2007 OLIFF & BERRIDGE, PLC		EXAMINER .		
P.O. BOX 19928			SHANKAR, VIJAY	
ALEXANDRIA, VA 22320			ART UNIT	PAPER NUMBER
			2629	
			MAIL DATE	DELIVERY MODE
			06/22/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)			
	10/828,438	NAKANISHI ET AL.			
Office Action Summary	Examiner	Art Unit			
	VIJAY SHANKAR	2629			
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply					
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period w - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tirr vill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	I. tely filed the mailing date of this communication. (35 U.S.C. § 133).			
Status					
1) Responsive to communication(s) filed on 21 Ap	<u>oril 2004</u> .	·			
· <u> </u>	, 				
3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims					
4) ☐ Claim(s) 1-12 is/are pending in the application. 4a) Of the above claim(s) is/are withdraw 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-12 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or	vn from consideration.				
Application Papers					
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) acce Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Ex	epted or b) objected to by the liderawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	e 37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).			
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received.					
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08)	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	ate			
Paper No(s)/Mail Date 4/21/04.					

Application/Control Number: 10/828,438 Page 2

Art Unit: 2629

DETAILED ACTION

Priority

1. Receipt is acknowledged of papers submitted under 35 U.S.C. 119(a)-(d), which papers have been placed of record in the file.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 3. Claims 1-12 are rejected under 35 U.S.C. 102(e) as being anticipated by LeChevalier (US 7,050,024 B2).

Regarding Claim 1, LeChevalier teaches an electro-optical device, comprising: an electro-optical element with a current-based data signal defining a tonal gradation level of pixels, and supplied to data lines, and with a luminance set in response to a driving current flowing from a power source voltage to a voltage lower in level than the power source voltage (Figs.2-4; Col.8, line 23- Col.12, line 43); the data lines arranged for respective pixels; power source lines to supply the pixels with the power source voltage (Figs.2-4; Col.8, line 23- Col.12, line 43); signal transfer lines; a first switching element to control electrical conduction between the data line and the

Art Unit: 2629

signal transfer line (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33); and a second switching element to control electrical conduction between the power source voltage and the signal transfer line, (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33); during a first mode (same as precharge period) in which the data signal is supplied to the data line not through the first switching element, the first switching element is set to be in a non-conductive state while the second switching element is set to be in a conductive state, (Column 3, line 1- Col.5, line 50) and during a second mode (same as exposure period) in which a signal different from the data signal is supplied to the data line through the first switching element, the first switching element is set to be in a conductive state while the second switching element is set to be in a non-conductive state (Column 3, line 1- Col.5, line 50). Also, see Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33.

Regarding Claim 2, LeChevalier teaches the electro-optical device further comprising: a first transistor that writes data to a capacitor in response to the data signal flowing through a data signal channel; and a second transistor arranged along the signal transfer line between the first switching element and the second switching element, having the same characteristics as the first transistor, and is configured in a diode-mode connection. (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33).

Regarding Claim 3, LeChevalier teaches an electro-optical device, comprising: an electro-optical element with a current-based data signal defining a tonal gradation level of pixels, supplied to data lines and with a luminance set in response to a driving current; the data lines arranged for respective pixels (Figs.2-4; Col.8, line 23- Col.12, line 43); signal transfer lines; and a switching element to control electrical conduction between the data line and the signal transfer line, during a first mode in which the data signal is supplied to the data line not through the switching element, the switching element is set to be in a non-conductive state while the signal transfer line is supplied with a predetermined voltage corresponding to a voltage that occurs in the data line when the data line is supplied with the data signal defining the lowest tonal gradation level, (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33); and during a second mode in which a signal different from the data signal is supplied to the data line through the switching element, (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33), the switching element is set to be in a conductive state while the supplying of the predetermined voltage to the signal transfer line is stopped. (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33)

Regarding Claim 4-7, LeChevalier teaches the electro-optical device the first mode being a normal mode to cause the electro-optical device to display an image under normal operating conditions, and the second mode being a test mode to test the electro-optical device; the signal transfer line is a test line connected to a pad to which

Art Unit: 2629

an external signal is supplied during the test mode; the power source lines including three lines respectively arranged for the three RGB colors, and the three RGB color power source lines have independent and respective signal transfer lines and switching elements. (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33).

Regarding Claim 8, LeChevalier teaches a method to drive an electro-optical device having an electro-optical element with a current-based data signal defining a tonal gradation level of pixels, and supplied to data lines, and with a luminance set in response to a driving current flowing from a power source voltage to a voltage lower in level than the power source voltage (Figs.2-4; Col.8, line 23- Col.12, line 43), the method comprising: setting, to be in a non-conductive state, a first switching element that controls electrical conduction between the data line arranged for respective pixels and a signal transfer line and setting, to a conductive state, (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33), a second switching element that controls electrical conduction between the power source voltage and the signal transfer line, during a first mode in which the data signal is supplied to the data line not through the first switching element (Figures 7-9, 11-12, Column 17, line 40-Col.24, line 65; Col.26, line 1 - Col.29, line 33); and setting the first switching element to be in a conductive state and setting the second switching element to be in a nonconductive state during a second mode in which a signal different from the data signal is

Page 6

Art Unit: 2629

supplied to the data line through the first switching element. (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33).

Regarding Claim 9, LeChevalier teaches the method to drive an electrooptical device according to claim 8, the electro-optical device including a first transistor
that writes data to a capacitor in response to the data signal flowing through the channel
thereof, and a second transistor that is arranged along the signal transfer line between
the first switching element and the second switching element, has the same
characteristics as the first transistor, and is configured in a diode-mode connection, the
method further comprises: supplying the power source voltage of the power source line
to the signal transfer line through the second transistor. (Figures 7-9, 11-12, Column
17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33).

Regarding Claim 10, LeChevalier teaches the method to drive an electrooptical device having an electro-optical element with a current-based data signal
defining a tonal gradation level of pixels, and supplied to data lines and with a
luminance set in response to a driving current (Figs.2-4; Col.8, line 23- Col.12, line 43),
the method comprising: setting, to be in a non-conductive state, a switching element
that controls electrical conduction between the data line and a signal transfer line, and
supplying the signal transfer line with a predetermined voltage corresponding to a
voltage that occurs in the data line when the data line is supplied with the data signal
defining the lowest tonal gradation level, (Figures 7-9, 11-12, Column 17, line 40-

Col.24, line 65; Col.26, line 1 - Col.29, line 33), during a first mode in which the data signal is supplied to the data line arranged for respective pixels, not through the switching element; and setting the switching element to be a conductive state (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33) and stopping the supplying of the predetermined voltage to the signal transfer line, during a second mode in which a signal different from the data signal is supplied to the data line through the switching element. (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33).

Regarding Claim 11-12, LeChevalier teaches the method to drive an electro-optical device the first mode being a normal mode to cause the electro-optical device to display an image under normal operating conditions, and the second mode being a test mode for testing the electro-optical device; the signal transfer line being a test line connected to a pad to which an external signal is supplied during the test mode. (Figures 7-9, 11-12, Column 17, line 40- Col.24, line 65; Col.26, line 1 - Col.29, line 33).

Application/Control Number: 10/828,438 Page 8

Art Unit: 2629

4. Any inquiry concerning this communication or earlier communications from the examiner should be directed to VIJAY SHANKAR whose telephone number is (571) 272-7682. The examiner can normally be reached on M-F 7:00 am - 4:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, BIPIN SHALWALA can be reached on (571) 272-7681. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

VIJAY SHANKAR Primary Examiner Art Unit 2629